

MULE™ ACCESSORIES

Insist on Kawasaki Genuine Accessories for the ultimate in quality and performance.

- 1 Aluminum hard top
- 2 Bed liner
- 3 Front floor mats
- 4 Rear floor mats
- 5 Cab structure
- 6 Front steel doors
- 7 Rear steel doors
- 8 Cab structure
- 9 Steel doors



See the full line of accessories at kawasaki.ca

SPECIFICATIONS	Mule™ 4010 Trans4x4* Diesel	Mule™ 4010 Trans4x4*	Mule™ 4010 4x4
Engine type	Four-stroke, 3-cylinder liquid-cooled OHV Diesel	Four-stroke, liquid-cooled, OHV 90° V-twin	Four-stroke, liquid-cooled, OHV 90° V-twin
Displacement	953cc	617cc	617cc
Bore x stroke	72 x 78 mm	76 x 68 mm	76 x 68 mm
Compression ratio	24.8:1	10.3:1	10.3:1
Carburetion	Mechanical Fuel Injection	Digital Fuel Injection (DFI)	Digital Fuel Injection (DFI)
Air filter	Snorkel-type with 2-stage dry replaceable element	Snorkel-type with 2-stage dry replaceable element	Snorkel-type with 2-stage dry replaceable element
Oil filter	Automotive-type spin-on canister	Automotive-type spin-on canister	Automotive-type spin-on canister
Ignition	Compression with glow plugs for starting	Digital electronic	Digital electronic
Electrical	12-volt DC; 52-amp hour battery, 40-amp alternator	12-volt DC; 14-amp hour battery, alternator	12-volt DC; 14-amp hour battery, alternator
Drive train	Kawasaki Automatic Power Drive System (KAPS): dual-range forward, neutral, reverse	Kawasaki Automatic Power Drive System (KAPS): dual-range forward, neutral, reverse	Kawasaki Automatic Power Drive System (KAPS): dual-range forward, neutral, reverse
Final drive	Shaft, selectable 4x4, Dual-Mode rear differential, front limited slip differential	Shaft, selectable 4x4, Dual-Mode rear differential, front limited slip differential	Shaft, selectable 4x4, Dual-Mode rear differential, front limited slip differential
Exhaust	Muffler with USFS-approved spark arrestor	Muffler with USFS-approved spark arrestor	Muffler with USFS-approved spark arrestor
Tires, front/rear	Tubeless, 23 x 11-10	Tubeless, 23 x 11-10	Tubeless, 23 x 11-10
Suspension, front	Independent, MacPherson strut-type	Independent, MacPherson strut-type	Independent, MacPherson strut-type
Suspension, rear	Semi-independent, De Dion axle with leaf/coil springs and hydraulic shocks	Semi-independent, De Dion axle with leaf/coil springs and hydraulic shocks	Semi-independent, De Dion axle with leaf springs and hydraulic shocks
Wheel travel, front/rear	100/70 mm (3.9/2.8 inches)	100/70 mm (3.9/2.8 inches)	100/70 mm (3.9/2.8 inches)
Steering	Electric power assisted/Rack & pinion	Electric power assisted/Rack & pinion	Electric power assisted/Rack & pinion
Brakes	Four-wheel sealed hydraulic drum; self-adjusting	Four-wheel sealed hydraulic drum; self-adjusting	Four-wheel sealed hydraulic drum; self-adjusting
Fuel capacity	24.2 litres (5.3 gallons)	23.5 litres (5.2 gallons)	23.5 litres (5.2 gallons)
Curb weight	788 kg (1,737 pounds)*	709 kg (1,563 pounds)*	638 kg (1,407 pounds)*
Dimensions (LxWxH)	3305 x 1486 x 1925 mm (130.1 x 58.5 x 75.8 in.)	3305 x 1486 x 1925 mm (130.1 x 58.5 x 75.8 in.)	3005 x 1575 x 1925 mm (118.3 x 62 x 75.8 in.)
Wheelbase	2165 mm (85.2 inches)	2165 mm (85.2 inches)	1870 mm (73.6 inches)
Ground clearance	180 mm (7.1 inches)	180 mm (7.1 inches)	175 mm (6.9 inches)
Cargo bed (LxWxH)	2-person: 1280 x 1212 x 287 mm (50.4x47.7x11.3 in.) (15.6 cu. ft.) 4-person: 770 x 1212 x 287 mm (30.3x47.7x11.3 inches) (9.4 cu. ft.)	2-person: 1280 x 1212 x 287 mm (50.4x47.7x11.3 in.) (15.6 cu. ft.) 4-person: 770 x 1212 x 287 mm (30.3x47.7x11.3 inches) (9.4 cu. ft.)	1175 x 1310 x 288 mm (46.3 x 51.6 x 11.3 inches) (15.6 cu. ft.)
Vehicle load capacity	740 kg (1,631 pounds)	603 kg (1,329 pounds)	603 kg (1,329 pounds)
Cargo bed load capacity	4-person mode: 318 kg (701 pounds) / 2-person mode: 499 kg (1100 pounds)	4-person mode: 182 kg (401 pounds) / 2-person mode: 363 kg (800 pounds)	363 kg (800 pounds)
Towing capacity	545 kg (1,200 pounds)	545 kg (1,200 pounds)	545 kg (1,200 pounds)
Turning radius (differential unlocked)	3.9 m (12.8 feet)	3.9 m (12.8 feet)	3.4 m (11.2 feet)
Top speed	40 km/h (25 mph) governed	38 km/h (24 mph) governed	38 km/h (24 mph) governed
Lights	(2) 35-watt, sealed-beam headlights with (2) 5/21-watt tail/stoplights	(2) 35-watt, sealed-beam headlights with (2) 5/21-watt tail/stoplights	(2) 35-watt, sealed-beam headlights with (2) 5/21-watt tail/stoplights

All 2009 Mule models are approved for Roll Over Protection System (ROPS). The structure meets ROPS requirements for wheeled tractors under SAE J1194, 7.1.1, 7.1.2, 7.4 and 7.5. The structure also meets the FMVSS 216 Roof Crush resistance requirement.

*Curb weights include all standard equipment, required fluids and full fuel tank.

One-Year Warranty

Your new MULE utility vehicle comes with Kawasaki's 12-month/unlimited mileage limited factory warranty. And you can extend your coverage inexpensively. Ask your dealer for details about the factory warranty and available extended coverage.

Up to Two Years Total Coverage*

Let Kawasaki protect your new machine for years to come* with the exclusive Good Times™ Protection Plan. This plan repairs or replaces most components free of charge if found defective in material or workmanship. Everything about the plan is easy: There's no deductible. It's honored at every authorized Kawasaki MULE dealer nationwide. It's transferable to another owner with no fee. Just ask your dealer how you can buy additional coverage of 12 or 24 months. Imagine, for just pennies a day, you can drive with no worry and no hassle. Just tell your dealer you want the Good Times Protection Plan.

*Depending on the program purchased.



MULE™ 4010 Trans4x4®:

Dark Royal Red • Woodsman Green

MULE™ 4010 Trans4x4® DIESEL:

Dark Royal Red • Woodsman Green

Safe Riding's More Fun

Always wear protective gear appropriate for the use of the vehicle. See the owner's manual for more information. Never operate motor vehicles under the influence of drugs or alcohol. Protect the environment. Obey laws and regulations that control the use of your vehicle. The Kawasaki MULE is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways.



Kawasaki subscribes to the guidelines of Tread Lightly!, a program dedicated to protecting the great outdoors through education and fostering responsible enjoyment of public lands.



MULE™ 4010 4x4:

Dark Royal Red • Woodsman Green

To view our complete accessory catalog, find your nearest dealer or take an in-depth tour of this machine visit:

kawasaki.ca/mule



P/N 99969-2329E

Printed in Canada

Action Photography: Professional rider on a closed course.

* All 2009 Mule models are approved for Roll Over Protection System (ROPS). The structure meets ROPS requirements for wheeled tractors under SAE J1194, 7.1.1, 7.1.2, 7.4 and 7.5. The structure also meets the FMVSS 216 Roof Crush resistance requirement.